



**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)


Patent Office
Canberra

REC'D 13 JUL 2004

WIPO

PCT

I, JULIE BILLINGSLEY, TEAM LEADER EXAMINATION SUPPORT AND
SALES hereby certify that annexed is a true copy of the Provisional specification
in connection with Application No. 2003903244 for a patent by MR ARVID
MURRAY JOHNSON as filed on 26 June 2003.



WITNESS my hand this
Eighth day of July 2004

J. Billingsley

JULIE BILLINGSLEY
TEAM LEADER EXAMINATION
SUPPORT AND SALES

BEST AVAILABLE COPY

Provisional Specification

Subject to the provisions of the Patents Act, information provided on this form may be made publicly available, including on the Internet.

Invention Title:

ROTATORY CRANKSHAFT

The invention is described in the following statement:

PAGE 1 OF 11

Line 00

01 This invention relates to an apparatus which produces
a mechanical conversion from or between rotary and linear
or non -rotary mechanical motion.
(subject matter)

Hitherto such conversions have been applied by a range of
mechanical an electro-mechanical devices, which are not
as suitable for some applications in mechanical and
nautical engineering.

10 eg. prior art; the Common Single and Double crankshaft,
the Jam Watt Sunwheel crankshaft, the Cog and ratchet
wheel crankshaft, the Scotch Yoke crankshaft, the Bell
crank, the epicycloidal crank
(prior art)

15

16 The object of this invention is to produce a
conversion from rotary to linear or non-rotary motion or
vice-versa , which is superior for some purposes.

19 (objects)

20 .According to this invention a diskus rotary crankshaft
.apparatus consists of:

.(A). a frame which houses the apparatus and to which
.components are attached rigidly or non -rigidly with
.appropriate constraints of motion.

26 .(B). a shaft which can rotate about its axis when driven by
.mechanical or electromechanical means and which
.incorporates a cam or an equivalent crank pin shaft.

.The cam can in the limit be circular as with an eccentric
30 .or shaped to apply the force more surely and exactly
.to the surface if forces are large or the tolerances
.are large and make the point of contact given by a circle
.insufficiently precise.

.(C). a quoit-disk which is engaged to the main shaft at
.the cam surface and the quoit-bearing of the condiskus.

.(D). a conrod and yoke with abearing which is engaged to
.the quoit disk at the yoke-bearing.

40 .

SARKKLARIOR IP AGENCY/PS/4A/B

PATENT SPECIFICATION

PAGE 3 OF 11

**41 .(E). a guide bar or slot to assist in the support of the
.yoke.**

**.(F).a slot or cylinder to guide and support the end of the
.conrod.**

**.(G).a configuration in which the mainshaft center of
.rotation is on a line perpendicular to the condiskus line of
.linear motion through the condiskus center or virtual
50 .center (the assymmetric configuration).**

**.(F). a configuration in which the mainshaft center of
.rotation is on a line which is the condiskus line of linear
.motion (the symmetric configuration) .**

.(statement of invention/consistory)

**. A rotatory crankshaft constructed in accordance with the
.invention will be described by way of example only, with
.reference to drawings Figures 1,2 , 3 and 4 .**

**60 .
.The frame is made to support the apparatus and main-
.shaft bearings and mechanical connections and**

PATENT SPECIFICATION

PAGE 4 OF 11

63 .control connections. Ref. Figure 1, G1 , G2 and Figure 4.

**.The mainshaft (MS1) is supported on bearings attached
.to the frame . Ref. Figure 4**

**.The mainshaft torque can drive the conrod via the
.condiskus or the conrod force can drive the mains shaft
.except at two neutral points. An appropriate periodic**

70 .force and flywheel or mass is required.

**.In the symmetric configuration the stroke and return
.stroke are symmetric. Ref. Figure 3**

**.In the assymmetric configuration the stroke and the return
.stroke are not symmetric. Ref. Figures 1 and 2.**

**.The dimensions and ratios of dimensions are not fixed
.but, must vary within limits. The cam must rotate
.within the limits of the condiskus.**

**.The surfaces G1 and G2 , Figure 1 , are constraints
.which produce a linear sliding motion. If the application**

**80 .required it , they could also move through an angle
.thus modifying , but not preventing motion.**

.(specific description)

84

PATENT SPECIFICATION

PAGE 5 OF 11

85 .The Claims defining the invention are as follows :

.Claim 1.

. This type of Rotatory crankshaft consists of :

**.(A) a main shaft and cam which is supported on bearings
and can rotate in a circular motion carrying the cam**

90 .with it.

**.(B) a condiskus inwhich the main shaft and cam rotate
within a quoit bearing.**

**.(C) a yoke and yoke bearing within which the condiskus
can rotate to the extent of the motion produced by the
mainshaft and cam.**

**.(D) a conrod attached to the yoke . The conrod moves
with a stroke and return stroke ,which can be symmetric
or assymmetric depending on the configuration of the
centers of the maim shaft, cam, and condiskus.**

**100 .(E) A restraint on the conrod head directing its motion,
usually linearly. An additional constraint , or slide guide
on the sides of the yoke if large forces are encountered.**

.Claim 2.

.The two configurations possible and the range of

106 .dimensions of the cam and the range of locations of the

PATENT SPECIFICATION

PAGE 6 OF 11

**107 .centers make it possible to design a wide range of
.strokes and motions of the conrod head.**

110 .Claim 3.

114 . Provisional




FIGURE 1

SARKKLARION IP AGENCY/PS4A/B

CONROD
AND
YOKE

CONDISKUS

BEARINGS

CENTERS 'C'





FIGURE 2

SARKKLARIOR IP AGENCY/PS4A/B






FIGURE 4

Handwritten signature and date: 1/11/2003
SARKKLARIOR IP AGENCY/PS4A/B

PATENT SPECIFICATION

PAGE 11 OF 11

PROVISIONAL

LAST PAGE

A. J. Johnson
25 16 12003

(MR ARVID MURRAY JOHNSON)

Name of Applicant(s)

25 16 12003

1 1

Date

SARKKLARIOR IP AGENCY/PS4R/B

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☒ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.